

# MEDIASTAFF® AD

## Kiosk Integration Platform™

### *Improving Business Has Never Been So Easy*

The MEDIASTAFF AD Kiosk Platform helps you serve more customers faster. An easy-to-use interface means more convenience and greater efficiency. It's accurate and built with state-of-the-art technology you can trust.

### *The Perfect Fit for Your Growing Business*

Higher ROI, lower cost, lower TCO. To keep pace with your growing business, PFU has created an unrivaled Kiosk Integration Platform™ that includes: Rugged kiosk hardware, intelligent middleware, a KIOSK SERVICE PLATFORM™ that facilitates the development and operations of web-based kiosk applications and our proprietary Remote Management System for monitoring and problem diagnosis, statistics, analytics and kiosk management.



#### **Special Features:**

- Signature pad with specialized middleware
- Counter-top or stand-alone model
- All peripherals can be replaced independently

#### **Standard I/O devices:**

- Signature pad
- Thermal printer
- Magnetic card reader
- Headphone jack

#### **Technology You Can Count On**

- Comprehensive kiosk platform accelerates your time to market while lowering application development, maintenance and servicing costs
- Rigorous testing of industrial quality components and peripherals ensures high reliability and availability
- Fanless design improves versatility and reliability

#### **Easy to Maintain**

- Operations management functions include diagnostic maintenance software
- Front panel opens outward for easy access to all devices

#### **Serving a Variety of Markets**

- Government
- Healthcare
- Education
- Financial Services

## Specifications Summary

OS	Microsoft <sup>®</sup> Windows <sup>®</sup> XP Professional	
Main Components	CPU	Intel <sup>®</sup> Celeron <sup>®</sup> 550 (2.0GHz)
	Memory	512MB
	HDD	80 GB
	Touch Screen	Analog resistive type
	Speakers	Stereo speakers
	Display	15-inch TFT color LCD monitor (16,770,000 colors, XGA)Angle of the Monitor: 50° to 90° (adjustable by 10° increments)
Standard Features	Proximity Sensor	Infrared reflection type
	Privacy Filter	Viewing angle: 60° (30° to left and 30° to right)
	Anti-glare coating	Anti-glare coating on Display
	Others	Door Sensor, guidance LEDs
I/O Devices	Signature Pad	1x5 LCD, Pressure-sensitive
	Magnetic Card Reader	Dip type, ISO #1/#2/#3
	Headphone Jack	3.5 mm stereo mini plug
	Thermal Printer	80mm wide, Printer Speed: max 250mm (9.84 inch)/s
External Interfaces	USB	USB2.0 × 4 ports (including maintenance port)
	Ethernet	1 - LAN 1000BASE-T/100BASE-TX/10BASE-T
Dimensions (W x D x H)	400 mm × 476 mm × 1272 mm (15.7" × 18.7" × 50.0") (when the Monitor angle is 50°. These dimensions do not include the base plate)	
Weight (including package content)	Approx. 30 kg (66lb)	
Weight of Stand	Approx. 31 kg (68.2lb)	
Regulations	FCC class A (USA), RoHS Compliant	

## Examples of Color Options



Black

Green

Silver

Blue

## Sales Office

### Headquarters & International Sales Office

PFU Systems, Inc.  
2055 Gateway Place, Suite 200  
San Jose, CA 95110  
Phone: +1.408.931.0655  
Fax: +1.408.451.2999

### Midwest Sales Office

PFU Systems, Inc.  
2600 Fernbrook Lane, Ste. 130  
Plymouth, MN 55447-4752  
Phone: +1.763.551.8261  
Fax: +1.763.551.8265

For more information please  
visit our website:  
[www.PFUsystems.com](http://www.PFUsystems.com)  
Or e-mail questions to:  
[Kiosksales@pfusystems.com](mailto:Kiosksales@pfusystems.com)