



a Fujitsu company

PFU Systems™

MEDIASTAFF™ ST *Simplify*

Kiosk Integration Platform™



- High Reliability
- Accelerate time-to-market
- Increase ROI
- Lower maintenance costs

Small footprint

Compact size makes economical use of valuable floor space

Flexible I/O configuration

Maximum two I/O devices

- Thermal Printer
- Magnetic Card Reader - motorized
- Contactless IC Card Reader/Writer
- 2D Barcode Reader

High availability; High reliability

- Rigorous testing of industrial quality components in a specially designed motherboard assures high availability to the end user
- Fanless design adds to the reliability and versatility

KIOSK SERVICE PLATFORM™

- Lowers kiosk application development cost
- Accelerates speed-to-market
- Significantly lowers maintenance and servicing costs

Easy maintenance features

- Operations management functions including diagnostic maintenance software to simplify kiosk maintenance
- Front panel opens outward for easy access to all devices

Market segments

- Retail applications
- Hospital applications
- Government applications



Specifications Summary

Feature		Specifications
OS		Microsoft® Windows® XP Professional
Main Components	CPU	Intel® Celeron® 550 (2.0GHz)
	Memory	512MB expandable to 1GB
	HDD	80GB
	Touch screen	Analog resistive type
	Speakers	Stereo speakers
	Display	15-inch TFT color LCD monitor (16,770,000 colors, XGA) Angle of the Monitor: 50° to 90° (adjustable by 10° increments)
Standard Features	Proximity Sensor	Infrared reflection type
	Privacy Filter	Viewing angle: 60° (30° to left and 30° to right)
	Anti-glare coating	Anti-glare coating on Display
	Others	Door Sensor, Guidance LED
I/O Device Options	Magnetic Card Reader	Motorized, JIS I (Track 1, Track 2)/JIS II
	2D Barcode Reader	2D and Linear barcode
	Thermal Printer	80mm wide, Printer Speed: max 250mm (9.84 inch)/second
	Contactless IC card reader/writer	Contactless IC card reader/writer for FeliCa®
Other Options		Auto On/Off Timer
External Interfaces	USB	USB2.0 × 4 ports (including maintenance port)
	LAN	1000BASE-T/100BASE-TX/10BASE-T × 1
Dimensions (W × D × H)		360 mm × 354 mm × 1,223 mm (14.4" × 14.16" × 48.92")
Weight		min: 42kg (92.4lb) / max: 46kg (101.2lb)

I/O Options



Thermal Printer





Magnetic Card Reader



Contactless IC Card Reader/Writer



2D Barcode Reader

-  Medium Blue
-  Off-White
-  Vivid Yellow
-  Vivid Red



For more information please visit our website:
www.PFUsystems.com
 Or e-mail questions to:
Kiosksales@pfusystems.com

Sales Office

Headquarters & International Sales Office

PFU Systems, Inc.
 2055 Gateway Place, Suite 200
 San Jose, CA 95110
 Phone: +1.408.451-2900
 Fax: +1.408.451-2999

Midwest Sales Office

PFU Systems, Inc.
 2600 Fernbrook Lane, Suite 130
 Plymouth, MN 55447-4752
 Phone: +1.763.551.8261
 Fax: +1.763.551.8265